

**PERIMETER SEAL**

**MAIN APPLICATION  
UNIVERSAL**

**PS-220B**

PROFILE	SEAL	STANDARD LENGTH	MAX LENGTH
ALUMINIUM	PVC (-10°C/+60°C)	1000	3000




**CONFIGURATION: BS-220B-A**

Profile	Silver matte anodised aluminium alloy
Seal	Black self-extinguish PVC
Fixing	Screws - Slotted holes upon request

**CONFIGURATION: BS-220B-N**


Profile	Black anodised aluminium alloy
Seal	Black self-extinguish PVC
Fixing	Screws - Slotted holes upon request

CODE	LENGTH mm	PROFILE COLOUR	SEAL COLOUR	BOX PCS
PS-220B-A1000	1000	SILVER	BLACK	50
PS-220B-N1000	1000	BLACK	BLACK	50



**PS-228B**

PROFILE	SEAL	STANDARD LENGTH	MAX LENGTH
ALUMINIUM	SILICONE (-40°C/+200°C)	1000	3000




**CONFIGURATION: BS-228B-A**

Profile	Silver matte anodised aluminium alloy
Seal	Grey self-extinguish silicone
Fixing	Screws - Slotted holes upon request

**CONFIGURATION: BS-228B-N**

Profile	Black anodised aluminium alloy
Seal	Grey self-extinguish silicone
Fixing	Screws - Slotted holes upon request

CODE	LENGTH mm	PROFILE COLOUR	SEAL COLOUR	BOX PCS
PS-228B-A1000	1000	SILVER	GREY	100
PS-228B-N1000	1000	BLACK	GREY	100



DIMENSIONS IN [mm] - THE MANUFACTURER RESERVES THE RIGHT TO MAKE TECHNICAL CHANGES WITHOUT NOTICE